ORTECH

Product Specification Sheet

LED LINEAR STRIP LIGHTS

OL-ST2-3CCT+WMS




HIGHLIGHTS

24" LED Strip Light Power & CCT adjusted, with Built-in Motion Sensor

- Built-in motion sensor with dip switches
- Factory setting: dims to 50%. Please see page 3 for more dimmer and sensor settings
- Daisy connection of up to 48 units per single power source running 347v
- Suspending installation and surface-mounted installation
- Diffused light, Damp location rated, Polycarbonate lens
- 5 year warranty

DIMENSIONS



Model	L×W×H (mm/inch)
OL-ST2-3CCT+WMS	609x74x83(mm) / 11.98"x2.91"x3.26"

SPECIFICATIONS

Model	OL-ST2-3CCT+WMS
Wattage	15W | 20W |25W
Voltage	AC120-347V
Lumens	1950lm |2600lm | 3250lm
Beam Angle | CRI	120° | 80
Lifetime	50000 hours
Dimmable	Yes(only 0-10v dimming available)
Warranty	5 years
Grade of Protection	IP20
Luminous Efficiency	130LM/W
Colour Temp.	3500K / 4000K / 5000K
Application	School / Hospital / Super market / Office / Warehouse
Operating Temp.	-20°C ~ +40°C
Case Quantities	10

ACCESSORIES



OL-ST2-LINK-KIT



SUS-KIT
(aircraft cable length: 4.92ft.)

DAISY CONNECTION

- 120V = **20 units**
- 277V = **38 units**
- 347V = **48 units**

www.ortechindustries.ca
1.888.543.6473
13376 Comber Way, Surrey, BC V3W 5V9
205 Summerlea Road, Brampton, Ontario
info@ortechindustries.com
604.543.6473


ORTECH


Product Specification Sheet

LED LINEAR STRIP LIGHTS


OL-ST2-3CCT+WMS

TESTING REPORT





APPLICATIONS



www.ortechindustries.ca

TF 1.888.543.6473

13376 Comber Way, Surrey, BC V3W 5V9

205 Summerlea Road, Brampton, Ontario

info@ortechindustries.com

604.543.6473

ORTECH
Product Specification Sheet

LED LINEAR STRIP LIGHTS

OL-ST2-3CCT+WMS

MOTION SENSOR SETTINGS

By selecting the combination of the DIP switches, sensor will be precisely set for different applications.

1	
●	100%
○	50%

Detection area
In this area, movement will be detected and able to trigger the sensor. 100% detection area is also known as the strong sensitivity.

2	3	
●	●	5s
●	○	30s
○	●	1min
○	○	10min

Hold-time
The period of light keeping 100% brightness after moving objects leave the detection area.

4	5	
●	●	Disable
●	○	50lux
○	●	10lux
○	○	2lux


Daylight threshold
Definition of the ambient brightness; only when the ambient brightness is lower that the preset specific lux amount, the sensor will work; when it's preset as "disable", the sensor works every time it detects motion regardless the ambient brightness.

6	7	
●	●	0s
●	○	30s
○	●	20min
○	○	+ ∞

Stand-by period
The period of light keeping low output before it's completely switched off. When it's preset as "∞", the light always keep at low output if no movement in the detection area and doesn't turn off.


8	9	
●	●	10%
●	○	20%
○	●	30%
○	○	50%

Stand-by dimming level
The definition of low output in the standby period.



Operating voltage	10-15VDC
Stand-by power	<0.5W
Stand-by power	≤1W
Detection area	50%/100%
Hold time	5s/30s/1min/10min
Daylight threshold	2Lux/10Lux/50Lux/Disable
Stand-by period	0s/30s/20min/+∞
Stand-by dimming level	10%/20%/30%/50%
Microwave frequency	5.8GHz±75MHz
Microwave power	<1mW
Mounting height	Max. 4.5m/14.76ft (ceiling mounted)
Detection range	Max.ø12m/39.36ft (ceiling mounted)
Operating temperature	-20°C~+60°C
Detection angle	30°-150°
Motion detection	0.5~3m/s
IP rating	IP20
Warranty	5 years

Detection Range



Reference	QTY.	Remarks	Project:
			Location:
			Architect:
			Engineer:
			Contractor:
			Submitted by:
			Date:

ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.

www.ortechindustries.ca
TF 1.888.543.6473
13376 Comber Way, Surrey, BC V3W 5V9
205 Summerlea Road, Brampton, Ontario
info@ortechindustries.com
604.543.6473