
SMSWR
LED SLIM FLUSH MOUNT







PART NUMBER	DIMENSIONS		
	A	B	C
SMSWR5	5.31" 135 mm	3.74" 95 mm	0.52" 13.2 mm
SMSWR7	7.00" 180 mm	5.47" 139 mm	0.52" 13.2 mm
SMSWR12	11.81" 300 mm	10.15" 258 mm	0.53" 13.5 mm
SMSWRNL7	7.44" 189 mm	6.18" 157 mm	0.65" 16.5 mm

FEATURES:
- 5CCT – 2700K, 3000K, 3500K, 4000K, 5000K
- D.O.B Technology
- Ultraslim 13mm thickness (Standard Fixture) / Ultraslim 16.5mm thickness (Night Light Fixture)
- Uniform Light Distribution
- Wet Location – Indoor Rated (Standard Fixture) / Damp Location – Indoor Rated (Night Light Fixture)
- 120Vac, 60Hz
- >80CRI
- Triac Dimmable
- Clip-on Black & Brushed Nickel Trims available (Not Available for Night Light Fixture)
- Contractor-friendly installation. Rotatable

EXTRA FEATURES AVAILABLE FOR NIGHT LIGHT FIXTURE
- NL Mode – 2200K (Available for Night Light Fixture Only)
- Night Light Feature on Back Trim – When in NL mode, 2200K and 3W
- To activate NL mode, turn switch off and on within 3 seconds.

CERTIFICATIONS:
- cETLus
- Meets ICES-005 Requirements

• **50,000 HOURS LIFE SPAN** • STORAGE TEMP: -10° - 50°C • OPERATING TEMP: -20° - 40°C • 5 YEARS WARRANTY

FAMILY	PART NUMBER	MODE	WATTAGE	VOLTAGE	COLOUR TEMP.	THD	POWER FACTOR	COLOUR	LENS
SMSWR	5-815CD-WH-FF	STANDARD FIXTURE	8 8W = 550LM	1 120V	5CD 5CCT - Changeable Colour Temperature 2700K / 3000K / 3500K / 4000K / 5000K	<50	>0.9	WH WHITE	FF FROSTED
	7-1215CD-WH-FF		12 12W = 840LM						
	12-2415CD-WH-FF		24 24W = 1680LM						
	NL7-1215CD-WH-FF	NL NIGHT LIGHT	12 12W = 840LM + 200LM						

ACCESSORIES

SNAP-ON TRIMS (NOT AVAILABLE FOR NIGHT LIGHT FIXTURE)





	BLACK	BRUSHED NICKEL
5"	SMSTM5-BL	SMSTM5-BN
7"	SMSTM7-BL	SMSTM7-BN
12"	SMSTM12-BL	SMSTM12-BN

WET LOCATION SMSWR DAMP LOCATION SMSWRNL DoB LED FLUSHMOUNT DIMMABLE 5 YEAR LIMITED WARRANTY

Intertek

CAN ICES-005 (B) / NMB-005 (B)

1850 Wilson Ave. · Toronto, ON · M9M 1A1 • Tel: 416.741.7336 · Fax: 416.741.9104 • Toll Free in Canada: 1.800.661.9610
For sales/service questions - sales@etlin.com • www.etlin-daniels.com