

ETLIN-DANIELS

CATALOG #		TYPE	
PROJECT		DATE	
PREPARED BY			

PRODUCT CODE: DLSWRH6-1513D-BN-FF | 6 INCH LED ULTRA SLIM PROFILE DOWNLIGHT/HEAT SINK





PRODUCT DESCRIPTION

The Etlin-Daniels DLSWRH6-1513D-BN-FF LED Ultraslim Profile Downlight is a modern, sleek looking energy efficient option for both new construction and retrofit/remodeling projects. It installs easily where there is limited ceiling space due to ductwork, joists and beams. With Etlin-Daniels IP65 rating, our Ultraslim Downlights are suitable for a wide range of both indoor & outdoor applications. Why waste time installing older space restrictive recessed options when the Etlin-Daniels Ultraslim Profile Downlight provides a quick install solution and elegant, superior quality lighting for both residential and commercial applications?

- Aluminum hardwire box with dimmable LED driver
- Includes a 7" cable from driver to fixture
- Built in Heat Sink

FEATURES

- LED light source
- 4" LED downlight
- Durable air tight Aluminum body
- Elegant Brushed Nickel finish
- Etched white Polycarbonate diffuser lens
- Includes two spring loaded clips for mounting to any ceiling material
- The slim profile design allows mounting under joists or duct work
- 50,000hrs L70 life
- Triac dimmable
- IC Air-tight rated
- Suitable for wet location - IP65
- 5 year limited warranty

PRODUCT SPECIFICATIONS (OPTICAL DATA)

PRODUCT SPECIFICATIONS (ELECTRICAL DATA)

LED TYPE	LED QTY	SYSTEM EFFICACY	LUMENS	COLOR TEMPERATURE	BEAM ANGLE	CRI	SYSTEM EFFICIENCY	VOLTAGE	POWER FREQ.	POWER EFFICIENCY	POWER FACTOR	HARMONIC DISTORTION
HONGLI TRONIC	36 CHIPS	60LM/W	900LM	3000K	120°	>80CRI	>90%	AC120V	50-60HZ	>80%	>0.98	<10%

PRODUCT SPECIFICATIONS

WATTAGE	FIXTURE MATERIAL	LIFE SPAN	STORAGE TEMP	OPERATING TEMP	PRODUCT DIMENSIONS	CARTON SIZE
15W	ALUMINUM/ POLYCARBONATE LENS	>50,000 HOURS	-40°C~+100°C -40°F~+212°F	-40°C~+85°C -40°F~+185°F	6.89 X 1.05 X 6.89 INCHES (175 X 27 X 175 MM)	17.32 X 11.02 X 9.05 INCHES (440 X 280 X 230MM)



ADDITIONAL INFORMATION	INSTALLATION METHOD	FIXTURE COLOR	CONTROL TYPE
	RECESSED CEILING MOUNT	BRUSHED NICKEL WITH WHITE ETCHED DIFFUSER	TRIAC DIMMABLE DRIVER INCLUDED

ETLIN-DANIELS

CATALOG #		TYPE	
PROJECT		DATE	
PREPARED BY			

PRODUCT CODE: DLSWRH6-1513D-BN-FF | **6 INCH LED ULTRA SLIM PROFILE DOWNLIGHT/HEAT SINK**

ENERGY STAR LISTING

ED Model Number	Technical Requirements Version	ENERGY STAR Unique ID	Listed Model Number	Category	Primary Use Designation
DLSWRH6-1513D-WH/BN-FF	ES2.0	2277711	DLSWRH6-1513D-**-FF	Indoor	Downlight Recessed

CERTIFICATIONS

Intertek · ENERGY STAR · RoHS · 5 YEAR LIMITED WARRANTY · WET LOCATION

DRIVER / LED CHIP

HONGLITRONIC · DIMMABLE

120V APPROVED DIMMERS

LUTRON:
CTCL-153PDH · CTCL-153P · CT-600P
LEVITON:
6672 · 6674
COOPER:
HCL453PTCCCV6

ACCESSORIES




72" EXTENSION CORD
PART# DLSEC-72



120" EXTENSION CORD
PART# DLSEC-120

PRE-MOUNTING PLATE FOR NEW CONSTRUCTION APPLICATIONS AVAILABLE. PLEASE CONTACT ETLIN-DANIELS.



PART NO#: DLS6-MP

ORDERING INFORMATION - DLSW SERIES

SERIES	IP RATING	SHAPE	HEAT DISSIPATION	SIZE	WATTAGE	VOLTAGE	COLOR TEMPERATURE	DIMMABLE	COLOR	LENS	TRIM
E.G. DLS	W	R	H	6	15	1	3	D	BN	F	F
DLS - DOWNLIGHT SLIM	W - WET LOCATION	R - ROUND	H - HEAT SINK	6 - 6"	15 = 15W	1 = 120V	3 = 3000K	D - TRIAC	BN - BRUSHED	F - FROSTED	F - FIXED
	IP65								NICKEL		

Head Office - 1850 Wilson Ave. · Toronto, ON · M9M 1A1 · **Tel:** 416.741.7336 · **Fax:** 416.741.9104
Toll Free: in Canada. 1.800.661.9610 · in USA. 1.888.762.5384 (SOCKETS4U)
www.etlin-daniels.com · For sales/service questions - sales@etlin.com