
EE300 / EX300 / EX220 SERIES
RUNNING MAN U24 UDC










ACCESSORIES AVAILABLE:
EXEC-WG-L - WIRE GUARD









• **17,000 HOURS LIFE SPAN** • STORAGE TEMP: -10º - 50ºC • OPERATING TEMP: 5º - 30ºC • 2 YEARS WARRANTY

SERIES	DIMENSIONS		
	A	B	C
EE300 °	13.07" 332 mm	9.21" 234 mm	1.81" 46 mm
EX300 °	12.20" 310 mm	7.56" 192 mm	2.13" 54 mm
EX220 °	13.19" 335 mm	8.86" 225 mm	2.00" 51 mm

SERIES	PART NUMBER	COLOUR	POWER	WATTAGE CONSUMED	CRI	INPUT POWER	BODY MATERIAL	COLOUR TEMP.	CERTIFICATIONS
EE300 °	WH-U24D-GU	WHITE	1 - 2W 2 - 0.5W	AC: 1 - 2W DC: 2 - 0.5W	80	AC: 1 - 2W DC: 2 - 0.5W	METAL	6000K - 6500K	cULus
EX300 °	WHM-U24D-GU	WHITE	2 - 3W	2 - 3W		2 - 3W	METAL		cCSAus
	BLM-U24D-GU	BLACK							
EX220 °	WH-U24D-GU	WHITE	2 - 3W	2 - 3W		2 - 3W	THERMO PLASTIC		

EE300 FEATURES:
- Full size LED Edge Lit Running Man sign.
- 180˚Angle Rotation of panel.
- White aluminum frame with PC panel.
- Universal Ceiling, wall, and side mount.

EX300 FEATURES:
- Durable steel housing.
- Universal Ceiling, wall, and side mount.

EX220 FEATURES:
- Compact UV stabilized Thermoplastic frame.
- Ceiling and wall mounting.

DESIGN:
- Single or double face.
- 3 pictograms included for directional orientation.
- IP20 – Dry location.
- High illuminance LED display.

CIRCUITS:
- AC 120-347V // DC 6-24VDC.
- 50/60Hz.
- Output Voltage - 3V
- Surge Protection – 1500V.

CERTIFICATIONS:
- EE300 cULus / EX300 & EX220 cCSAus
- Complies to CSA 22.2 #141-15
- Meets ICES-005 Requirements

c UL us LISTED
CAN ICES-005 (B) / NMB-005 (B)

1850 Wilson Ave. · Toronto, ON · M9M 1A1 • Tel: 416.741.7336 · Fax: 416.741.9104 • Toll Free in Canada: 1.800.661.9610
For sales/service questions - sales@etlin.com • www.etlin-daniels.com